

Claims

1. (Previously Presented) A transform coder computer system for audio signal processing comprising:

a transient detection component stored in computer system memory operating to process samples of an input signal to identify locations of transients in the input signal;

an open-loop window configuration component stored in computer system memory operating in response to the identified transient location to configure a first configuration of sizes of a plurality of transform input windows over the input signal selected from at least a first window size, a second window size, and a third window size, so as to place one or more windows of the first window size to encompass a region of the input signal having at least one identified transient location and place windows of the second size in areas of the input signal having no identified transient locations;

an encoding component stored in computer system memory for transform coding the input signal according to the first configuration of transform input window sizes, and for decoding to produce a reconstructed signal;

a quality measurement component stored in computer system memory operating to measure achieved quality of the reconstructed signal; and

a closed-loop window configuration component stored in computer system memory operating in response to the achieved quality measurement to adjust sizes of the transform input windows in the first configuration according to the achieved quality measurement to produce a second configuration of transform input windows for use in transform coding the input signal.

2. (Previously Presented) The transform coder of claim 1 wherein the open-loop window configuration component is further operative to place at least one transform input window of the third window size between the transform input windows of the first window size and those of the second size.

3. (Original) The transform coder of claim 1 wherein the closed-loop window configuration component operates to adjust sizes of the transform input windows in a current

portion of the input signal according to the achieved quality measurement of a preceding portion of the reconstructed signal.

4. (Original) The transform coder of claim 1 wherein:
the quality measurement component further operates to measure achieved perceptual quantization noise of the reconstructed signal for at least some of the transform input windows in the first configuration; and
the closed-loop window configuration component further operates to increase a minimum permitted window size of transform input windows for at least a portion of the input signal where the measure of achieved perceptual quantization noise exceeds an acceptable threshold.

5. (Original) The transform coder of claim 4 wherein:
the closed-loop window configuration component also operates to increase a minimum permitted window size of transform input windows for at least a portion of the input signal when utilization of a rate control buffer exceeds a fullness threshold.

6. (Original) The transform coder of claim 1 wherein:
the quality measurement component further operates to detect pre-echo in the reconstructed signal; and
the closed-loop window configuration component further operates to decrease window size of at least one transform input window in at least a portion of the input signal where pre-echo is detected.

7. (Previously Presented) The transform coder of claim 6 wherein said decreasing the window size comprises decomposing a frame in which pre-echo is detected into transform input windows of the first window size; the first window size being smaller than the second window size and the first window size being smaller than the third window size.

8. (Previously Presented) The transform coder of claim 6 wherein said decreasing the window size comprises decomposing a transform input window in the first configuration in which pre-echo is detected into transform input windows of the first window size; the first

window size being smaller than the second window size and the first window size being smaller than the third window size.

9. (Canceled)

10. (Previously Presented) In a computer-enabled transform coder, a method of adaptively selecting transform window size for signal processing, the method comprising:

detecting locations of transients in an input signal;

for a frame of the input signal in which no transient location is detected, configuring size of a transform window to be a first window size;

for a frame of the input signal in which at least one transient location is detected, configuring sizes of a plurality of transform windows in the frame to comprise a consecutive set of at least one second-size window substantially encompassing the transient locations in the frame and at least one third-size window before the transient, where the second window size is smaller than the first window size and where the third window size is intermediate to the first and second window sizes;

transform encoding the input signal according to a first transform window configuration including the configured sizes of transform windows;

measuring achieved perceptual quality of the transform-encoded signal;

storing the measured perceptual quality in memory associated with the transform coder;

retrieving the measured perceptual quality from memory;

using the retrieved measured perceptual quality, re-configuring the size of at least some of the transform windows configured in the first transform window configuration according to the measured perceptual quality to produce a second transform window configuration; and

transform encoding the input signal according to the second transform window configuration.

11. (Previously Presented) In a computer-enabled transform coder, a method of adaptively selecting transform window size for audio signal processing, the method comprising:

detecting locations of transients in an input signal;

for a frame of the input signal in which no transient location is detected, configuring size of a transform window to be a first window size;

for a frame of the input signal in which at least one transient location is detected, configuring sizes of a plurality of transform windows in the frame to comprise a consecutive set of at least one second-size window substantially encompassing the transient locations in the frame and at least one third-size window before the transient, where the second window size is smaller than the first window size and where the third window size is intermediate to the first and second window sizes;

transform encoding the input signal according to a first transform window configuration including the configured sizes of transform windows;

measuring achieved perceptual quality of the transform-encoded signal for at least some of the configured transform windows;

storing the measured perceptual quality in memory associated with the transform coder;

retrieving the measured perceptual quality from memory;

using the retrieved measured perceptual quality, increasing sizes of at least some transform windows in the first transform window configuration where the achieved perceptual quality of the transform-encoded signal exceeds an acceptable level to produce a second transform window configuration;

transform encoding the input signal according to the second transform window configuration.

12. (Original) The method of claim 11 further comprising:

increasing sizes of at least some transform windows in the first transform window configuration to produce the second transform window configuration when utilization of a rate control buffer exceeds a fullness threshold.

13. (Previously Presented) In a computer-enabled transform coder, a method of adaptively selecting transform window size for audio signal processing, the method comprising:
detecting locations of transients in an input signal;

for a frame of the input signal in which no transient location is detected, configuring size of a transform window to be a first window size;

for a frame of the input signal in which at least one transient location is detected, configuring sizes of a plurality of transform windows in the frame to comprise a consecutive set of at least one second-size window substantially encompassing the transient locations in the frame and at least one third-size window before the transient, where the second window size is smaller than the first window size and where the third window size is intermediate to the first and second window sizes;

transform encoding the input signal according to a first transform window configuration including the configured sizes of transform windows;

increasing sizes of at least some transform windows in the first transform window configuration to produce a second transform window configuration when utilization of a rate control buffer exceeds a fullness threshold;

storing the second transform window configuration in memory associated with the transform coder;

retrieving the second transform window configuration from memory; and

using the retrieved second transform window configuration, transform encoding the input signal according to the second transform window configuration.

14. (Previously Presented) In a computer-enabled transform coder, a method of adaptively selecting transform window size for audio signal processing, the method comprising: detecting locations of transients in an input signal;

for a frame of the input signal in which no transient location is detected, configuring size of a transform window to be a first window size;

for a frame of the input signal in which at least one transient location is detected, configuring sizes of a plurality of transform windows in the frame to comprise a consecutive set of at least one second-size window substantially encompassing the transient locations in the frame and at least one third-size window before the transient, where the second window size is smaller than the first window size and where the third window size is intermediate to the first and second window sizes;

transform encoding the input signal according to a first transform window configuration including the configured sizes of transform windows;

measuring achieved perceptual quality of the transform-encoded signal for at least some of the configured transform windows;

storing the measured perceptual quality in memory associated with the transform coder;

retrieving the measured perceptual quality from memory;

using the retrieved measured perceptual quality, increasing sizes of transform windows in a frame in the first transform window configuration to an increased minimum size greater than the second window size where the achieved perceptual quality of the transform-encoded signal in the frame exceeds an acceptable level to produce a second transform window configuration;

transform encoding the input signal according to the second transform window configuration.

15. (Previously Presented) In a computer-enabled transform coder, a method of adaptively selecting transform window size for audio signal processing, the method comprising:

detecting locations of transients in an input signal;

for a frame of the input signal in which no transient location is detected, configuring size of a transform window to be a first window size;

for a frame of the input signal in which at least one transient location is detected, configuring sizes of a plurality of transform windows in the frame to comprise a consecutive set of at least one second-size window substantially encompassing the transient locations in the frame and at least one third-size window before the transient, where the second window size is smaller than the first window size and where the third window size is intermediate to the first and second window sizes;

transform encoding the input signal according to a first transform window configuration including the configured sizes of transform windows;

detecting pre-echo in the transform-encoded signal;

decreasing sizes of at least some transform windows in the first transform window configuration in a portion of the transform-encoded signal where pre-echo is detected to produce a second transform window configuration;

storing the second transform window configuration in memory associated with the transform coder;

retrieving the second transform window configuration from memory;

using the second transform window configuration, transform encoding the input signal according to the second transform window configuration.

16. (Previously Presented) The method of claim 15 wherein measuring pre-echo comprises:

measuring a vector of achieved perceptual quality of a plurality of segments of the transform-encoded signal, the segments being smaller than the second window size;

measuring a global achieved perceptual quality of at least a portion of the transform-encoded signal; and

determining that pre-echo exists at location of the input signal corresponding to components of the achieved perceptual quality in the vector that exceed a significance multiple of the global achieved perceptual quality.

17. (Original) The method of claim 15 wherein decreasing sizes of at least some transform windows in the first window configuration comprises:

decomposing configured transform windows in the first window configuration that form a frame in which pre-echo is detected into minimum size transform windows to produce the second transform window configuration.

18. (Original) The method of claim 15 wherein decreasing sizes of at least some transform windows in the first window configuration comprises:

decomposing configured transform windows in the first window configuration in which pre-echo is detected into smaller size windows to produce the second transform window configuration.

19. (Previously Presented) In a computer-enabled transform coder, a method of adaptively selecting transform window size for audio signal processing, the method comprising:

detecting locations of transients in an input signal;

for a frame of the input signal in which no transient location is detected, configuring size of a transform window to be a first window size;

for a frame of the input signal in which at least one transient location is detected, configuring sizes of a plurality of transform windows in the frame to comprise a consecutive set of at least one second-size window substantially encompassing the transient locations in the frame, where the second window size is smaller than the first window size;

transform encoding the input signal according to a first transform window configuration including the configured sizes of transform windows;

measuring achieved perceptual quality of the transform-encoded signal;

storing the measured perceptual quality in memory associated with the transform coder;

retrieving the measured perceptual quality from memory;

using the retrieved measured perceptual quality, re-configuring the size of at least some of the transform windows configured in the first transform window configuration according to the measured perceptual quality to produce a second transform window configuration; and

transform encoding the input signal according to the second transform window configuration.

20. (Original) The method of claim 19 wherein said re-configuring the size of at least some of the transform windows comprises:

increasing sizes of at least some transform windows in the first transform window configuration where the achieved perceptual quality of the transform-encoded signal exceeds an acceptable level to produce the second transform window configuration.

21. (Original) The method of claim 19 wherein said re-configuring the size of at least some of the transform windows comprises:

increasing sizes of at least some transform windows in the first transform window configuration to produce the second transform window configuration when utilization of a rate control buffer exceeds a fullness threshold.

22. (Original) The method of claim 19 wherein said re-configuring the size of at least some of the transform windows comprises:

increasing sizes of transform windows in a frame in the first transform window configuration to an increased minimum size greater than the second window size where the

achieved perceptual quality of the transform-encoded signal in the frame exceeds an acceptable level to produce the second transform window configuration.

23. (Original) The method of claim 19 further comprising:
detecting pre-echo based on said measuring achieved perceptual quality of the transform-encoded signal; and
decreasing sizes of at least some transform windows in the first transform window configuration in a portion of the transform-encoded signal where pre-echo is detected to produce the second transform window configuration.

24. (Original) The method of claim 23 wherein measuring pre-echo comprises:
measuring a vector of achieved perceptual quality of a plurality of segments of the transform-encoded signal, the segments being smaller than the second window size;
measuring a global achieved perceptual quality of at least a portion of the transform-encoded signal; and
determining that pre-echo exists at location of the input signal corresponding to components of the achieved perceptual quality in the vector that exceed a significance multiple of the global achieved perceptual quality.

25. (Original) The method of claim 23 wherein decreasing sizes of at least some transform windows in the first window configuration comprises:
decomposing configured transform windows in the first window configuration that form a frame in which pre-echo is detected into minimum size transform windows to produce the second transform window configuration.

26. (Original) The method of claim 23 wherein decreasing sizes of at least some transform windows in the first window configuration comprises:
decomposing configured transform windows in the first window configuration in which pre-echo is detected into smaller size windows to produce the second transform window configuration.

27. (Previously Presented) In a computer-enabled transform coder, a method of adaptively selecting transform window size for audio signal processing, the method comprising:
detecting locations of transients in a current frame of an input signal;
measuring achieved perceptual quality of at least one prior transform-encoded frame of the input signal;

storing the measured achieved perceptual quality in memory associated with the computer-enabled transform coder;

using the stored measured achieved perceptual quality, determining a minimal window size for the current frame based on the measured achieved perceptual quality of the at least one prior transform-encoded frame;

for a first case in which no transient location is detected in the current frame, configuring size of a transform window to be a first window size;

for a second case in which at least one transient location is detected in the current frame of the input signal, configuring sizes of a plurality of transform windows in the frame to comprise a consecutive set of at least one second-size window substantially encompassing the transient locations in the frame, where the second window size is the minimal window size for the current frame; and

transform encoding the current frame of the input signal according to the configured sizes of transform windows.

28. (Original) The method of claim 27 wherein said determining the minimal window size comprises:

increasing the minimal window size for the current frame if the achieved perceptual quality of the at least one prior transform-encoded frame of the input signal exceeds an acceptable level.

29. (Previously Presented) The method of claim 27 wherein said determining the minimal window size comprises:

increasing the minimal window size for the current frame if utilization of a rate control buffer exceeds a fullness threshold.

30. (Previously Presented) The method of claim 27 further comprising:
detecting pre-echo; and
decreasing sizes of at least some transform windows where pre-echo is detected.
31. (Original) The method of claim 30 wherein measuring pre-echo comprises:
measuring a vector of achieved perceptual quality of a plurality of segments of the input signal, the segments being smaller than the second window size;
measuring a global achieved perceptual quality of the at least one prior transform-encoded frame; and
determining that pre-echo exists at location of the input signal corresponding to components of the achieved perceptual quality in the vector that exceed a significance multiple of the global achieved perceptual quality.
32. (Original) The method of claim 30 wherein the decreasing sizes comprises:
if pre-echo is detected, decomposing all configured transform windows in the current frame to the minimal window size.
33. (Original) The method of claim 30 wherein the decreasing sizes comprises:
decomposing only those configured transform windows in the current frame in which pre-echo is detected to the minimal window size.
34. (Currently Amended) A ~~program storage~~ computer readable medium having instructions that when executed ~~a transform coding program executable~~ on an audio processing device ~~to~~ perform a method of adaptively selecting transform window size for audio signal processing, the method comprising:
detecting locations of transients in an input signal;
for a frame of the input signal in which no transient location is detected, configuring size of a transform window to be a first window size;
for a frame of the input signal in which at least one transient location is detected, configuring sizes of a plurality of transform windows in the frame to comprise a consecutive set

of at least one second-size window substantially encompassing the transient locations in the frame, where the second window size is smaller than the first window size;

transform encoding the input signal according to a first transform window configuration including the configured sizes of transform windows.

measuring achieved perceptual quality of the transform-encoded signal;

re-configuring the size of at least some of the transform windows configured in the first transform window configuration according to the measured perceptual quality to produce a second transform window configuration; and

transform encoding the input signal according to the second transform window configuration.

35. (Currently Amended) The ~~program storage~~ computer readable medium of claim 34 wherein said re-configuring the size of at least some of the transform windows comprises:

increasing sizes of at least some transform windows in the first transform window configuration where the achieved perceptual quality of the transform-encoded signal exceeds an acceptable level to produce the second transform window configuration.

36. (Currently Amended) The ~~program storage~~ computer readable medium of claim 34 wherein said re-configuring the size of at least some of the transform windows comprises:

increasing sizes of at least some transform windows in the first transform window configuration to produce the second transform window configuration when utilization of a rate control buffer exceeds a fullness threshold.

37. (Currently Amended) The ~~program storage~~ computer readable medium of claim 34 wherein said re-configuring the size of at least some of the transform windows comprises:

increasing sizes of transform windows in a frame in the first transform window configuration to an increased minimum size greater than the second window size where the achieved perceptual quality of the transform-encoded signal in the frame exceeds an acceptable level to produce the second transform window configuration.

38. (Currently Amended) The ~~program storage~~ computer readable medium of claim 34 wherein the method further comprises:

detecting pre-echo based on said measuring achieved perceptual quality of the transform-encoded signal; and

decreasing sizes of at least some transform windows in the first transform window configuration in a portion of the transform-encoded signal where pre-echo is detected to produce the second transform window configuration.

39. (Currently Amended) The ~~program storage~~ computer readable medium of claim 38 wherein measuring pre-echo comprises:

measuring a vector of achieved perceptual quality of a plurality of segments of the transform-encoded signal, the segments being smaller than the second window size;

measuring a global achieved perceptual quality of at least a portion of the transform-encoded signal; and

determining that pre-echo exists at location of the input signal corresponding to components of the achieved perceptual quality in the vector that exceed a significance multiple of the global achieved perceptual quality.

40. (Currently Amended) The ~~program storage~~ computer readable medium of claim 38 wherein decreasing sizes of at least some transform windows in the first window configuration comprises:

decomposing configured transform windows in the first window configuration that form a frame in which pre-echo is detected into minimum size transform windows to produce the second transform window configuration.

41. (Currently Amended) The ~~program storage~~ computer readable medium of claim 38 wherein decreasing sizes of at least some transform windows in the first window configuration comprises:

decomposing configured transform windows in the first window configuration in which pre-echo is detected into smaller size windows to produce the second transform window configuration.

42-49. (Canceled)